



SPRINT - PRIMAVERA 50 4T3V - TECHNICAL SPECIFICATIONS

ENGINE	3-valve 4-stroke single cylinder i-get catalysed
DISPLACEMENT	49 cc
BORE X STROKE	39 mm x 41,4 mm
MAX POWER AT THE CRANK SHAFT	2.2 kW - 3 HP - at 7,500 rpm
MAX TORQUE	2.9 Nm at 7,000 rpm
CONSUMPTION	40 km/l
CO2 EMISSIONS COMPLIANCE	57 g/km
FUEL SYSTEM	Electronic Injection
COOLING	Forced air
STARTER	Electric
GEARBOX	CVT automatic with torque server
CLUTCH	Automatic dry centrifugal with shock absorbers
LOAD-BEARING STRUCTURE	Sheet steel shell with welded structural reinforcements
FRONT SUSPENSION	Single arm with helical spring and hydraulic shock absorber
REAR SUSPENSION	Helical spring with single hydraulic shock absorber
FRONT BRAKE	Stainless steel Ø 220 mm disc with hydraulic control
REAR BRAKE	Ø 140 mm drum with mechanical control
ABS/ASR SYSTEM	-
FRONT TYRE	Tubeless 110/70 - 12"
REAR TYRE	Tubeless 120/70 - 12"
LENGTH/WIDTH/WHEELBASE	1,870 / 735 / 1,330 mm
SEAT HEIGHT	790 mm
FUEL TANK CAPACITY	7,5 litres
EMISSIONS COMPLIANCE	Euro 5